



MAIN FEATURES

- 4000 W on the go.
- Handy operation.
- High quality product.
- Compact weather proof design.
- 7.5 KVA & 9 KVA generator output.
- Protection against high temperature and low oil pressure.

TRAILER

Chassis:

Heavy formed welded steel, two wheels, single axle, torsion bar suspension and 4 adjustable stabilizer support. 50 mm towing ball - 185 R14 wheels and tires.

Housing:

Rugged fully enclosed, structural frame, corrosive resistant, carbonized steel frame. Polyester, powder painted. Weather proof canopy with 2 lockable lift up doors on stainless steel hinges.

Fuel tank:

50 hours operation capacity with manhole filler cap..

LIGHT TOWERS

ELECTRICAL SYSTEM:

Lighting system:

4 x 1000 watt wide area floodlights.

Fixtures:

High efficiency, rugged non-corrosive cast aluminum housing with 4 fixtures and tempered glass lens.

Ballastic System: Open core and coil type with external capacitors mounted in 4 individual compartments.

Wiring: Oil and grease resistant S-O type cable with weather protected, twist lock connectors on all external wiring.

Convenience Receptacles:

2 x 230 volts, 20 amp and 1 x 230 volt, 30 amp twist lock receptacles with circuit protection.

Safety features:

All short circuit and overload protections.

Instrumentation:

Elapsed time meter, oil pressure gauge, battery charging ammeter and engine ignition switch.

MAST:

Fully extended 9 meters height - 360 degrees rotation, Manual mast lock and manual winch for raising and lowering.

GENERATING SET:

9 KVA @ 1500 Rpm
Perkins Engine - 404D-11G
LEROY SOMER Alternator - LSA40VS2

7.5 KVA @ 1500 Rpm
Lister Engine - LPW2
LEROY SOMER Alternator - LSA40VS2

NOTE:

THIS DRAWING IS PROVIDING FOR REFERENCE ONLY AND SHOULD NOT BE USED FOR PLANNING INSTALLATION OTC RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE.

OVERSEAS TRADING CENTER

P.O. BOX 8266 SHARJAH (A4-075)

SAIF ZONE U.E.A.E

Tel: +971 6 5575888 Website: www.otcglobal.net

Fax: +971 6 5575999 www.otcpower.net